MAINTENANCE RELATED PARTS

CONTROL MAGNETIC FORCE!



Just rub inside the magnetizer & demagnetizer with driver end. Easy magnetizing and demagnetizing!

MAGNETIZER & DEMAGNETIZER

CODE	PRICE
674-0900320 CLICK	¥500
RODY : RESIN INSIDE : DERMANENT MAGNET	

- SIZE: 50 × 51 × 29 (mm) SOLD EACH
- * There are some metals that are not able to get magnetic.
- ** There might not be demagnetic completely.** Do not place this tool to somewhere close to some equipment that get affected by magnet.



WHEN DEMAGNETIZING





EXCHANGE TIRES WITHOUT HURTING WHEELS!



Removing and installing tires safely with flat type

TIRE LEVER (260mm)

CODE	PRICE	
674-0500210 CLCK	¥1,800	
● UNIVERSAL ● TOOL STEEL ● LENGTH: 260mm ● SOLD IN PAIRS		



IMAGE

WHEN MAGNETIZING

NOW ON SALE!



RIM PROTECTOR PRICE: ¥600 CODE: 674-0800500

For 1/4sq-6.35mm & 3/8sq-9.5mm SOCKET!



Must for motorcycle maintenance! Combination T-shape wrench for 2 types of insert type (1/4 sq-6.35mm & 3/8 sq-9.5mm) sockets & 1/4 hex bit holder newly released!



1/4 hex big holder usable with head sliding (see right illustration)

COMBINATION T-SHAPE

_		
	CODE	PRICE
L	OODL	TTIIOL
Г		
	674-0800100 GLCX	¥2.600
	074-0000100 Amm	1 2,000
Т	A LINIU/EDOAL A INICEDT ANICHE	. 1 /4 0 0 (0) 0 /0

● UNIVERSAL ● INSERT ANGLE: 1/4 sq-6.35mm (2 places) 3/8 sq-9.5mm (1 place) (WHEN SLIDING HEAD: 1/4 HEX BIT HOLDER (INSERT LENGTH 6.35mm)) ● SHAFT LENGTH: 240mm (WHEN SLIDING: 250mm) HANDLE LENGTH: 140mm SOLD EACH





Tightening speedy



Tightening firmly

