

# ENGINE GUARD

CODE	(BLACK) 550-1470000
APPLICATION	CT125 HUNTER CUB (JA55) ※ JA65 is not compatible.

● Thank you for purchasing Kitaco product. Read and understand the instruction before installing.

## ATTENTION (MUST READ)

- This product is for dress up and minimize the damage by accident. (This is not designed for heavy use.) Do not use for other purposes.
  - This product is designed and made exclusive for application vehicles, do not use other models. Do not modify the way which is not listed or it will cause damage and trouble.
  - We are not responsible for violation of law or damages and accidents caused by assembling mistake and improper setting.
  - Please ask authorized mechanic for assembling and setting.
  - Refer to the manufacturer service manual when installation.
  - Bolts and nuts may get loosen by engine vibration. Make sure not to loosen any bolts and nuts before driving.
- ※ Metal/resin/alumite products get discolored/rust for ages as well as how to use. Please understand when using.

❗ Do not apply excessive force to this product when using rope or tie to deliver the vehicle. It might damage this product or surrounding parts.

⊘ This product cannot protect or prevent engine from under heavy use. It might cause of breaking this product or surrounding parts.

## HOW TO INSTALL

### ADVICE!

When installing, install bolt and nut temporarily for adjusting each parts. (If tighten firmly while temporarily assembling, it might cause of unable to install such as the bolt hole does not match, etc). After temporarily assembling, tighten firmly following torque with adjusting each parts.

- Install Kitaco engine guard to normal under cover pipe (L/R) installation position. (Disassemble under pipe as illustration below.)
- Make sure engine guard is not loosen before riding.

STANDARD TORQUE	
BOLT / NUT SIZE	N·m (FLANGE TYPE)
6 mm (SH flange bolt included)	10
6 mm FLANGE (NSHF included)	(12)
8 mm	22 (27)

