

# AERO VISOR

CODE	SMOKE : 670-1833100
APPLICATION	GB350S (NC59) ※ GB350 is not compatible. (Head light shape is different.)
REMARK	Cannot install with USB POWER SUPPLY (80-757-18290) together.

Thank you for purchasing Kitaco product. Read and understand the instruction before installing.


## ATTENTION (MUST READ)

- This product is designed and made exclusive for application vehicles, do not use other models. Do not modify the way which is not listed or it will cause damage and trouble.
- We are not responsible for violation of law or damages and accidents caused by assembling mistake and improper setting.
- Please ask authorized mechanic for assembling and setting.
- Refer to the manufacturer service manual when installation.
- Bolts and nuts may get loosen by engine vibration. Make sure not to loosen any bolts and nuts before driving.
- This instruction sheet is for the instruction for genuine condition.

## HOW TO TAKE CARE THE SCREEN

### ⚠ ATTENTION

- Under the direct sunlight, it might occur the trouble like deformation, fire, etc, because of condensing phenomenon due to concave mirror effect. Be careful when parking.
- When parking under direct sunlight, please block screen from direct sunlight by soft cloth, etc.
- When windy day, it is susceptible to wind, please drive at reduced speed.
- When parking with body cover on, choose a shaded and well-ventilated place. If you park under the high heat with body cover on, heat builds up inside, it may cause deformation.
- Be careful not to adhere battery fluid, brake fluid. It breaks screen plastic.
- Do not apply excessive force, hard bend, it may cause of broken.
- Please inspect sometimes not to loosen and backlash for additional tightening.
- Welnut is aging by ultraviolet rays and aging, if deterioration is remarkable, please change to new one.
- If there is a hard scratch and break, please change to new one because it might fall off.
- When screen get dirt, wipe with soft cloth or sponge with lots of water. Screen is easy to get hurt, do not use blush.
- If screen gets heavy dirt, please use neutral detergent. (Using abrasive powder, etc is prohibited.) Do not use organic solvent like acid/alkaline detergent, gasoline, benzine, sinner, etc.



PACKING LIST (Refer to the figure & illustration on right side.)				
FIGURE	NAME	CODE	QTY	
1	SCREEN	SMOKE	670-9000101	x1
2	SCREEN STAY	L	670-1833101	x1
3	SCREEN STAY	R	670-1833102	x1
4	STEPPED COLLAR		670-1833103	x4
5	PAN HEAD(+) SCREW(B)	M5x20	052-0503020	x4
6	WASHER (B)	12x5,2xT1,5mm	090-0914005	x8
7	WELNUT	C550 M5x0.8	678-0500001	x4
8	CAP BOLT	M5x25	050-0500025	x4

## HOW TO INSTALL

### ※ADVICE

- When installing, tighten each bolts temporarily, then tighten finally with adjusting left and right balance.
- 1) Remove head light socket bolt.
  - 2) Install stay temporarily to socket bolt hole position with attached bolt, washer and spacer collar.
  - 3) Install screen to LR stay with attached welnut, screw and washer while adjusting left and right balance.
  - 5) After finished adjusting balance of all parts, tighten each bolts firmly.

### ATTENTION!

- If there is a hard degradation like a blem, fatigue and wear etc on the reuse parts, please change to new ones.
- Before installation, make sure to match the hole position not to break head light cover.

