

AERO VISOR		
CODE	DARK SMOKE : 670-1870100	
APPLICATION	CL250 (MC57) /500 (PC68)	

Thank you for purchasing Kitaco product. Read and understand the instruction before installing.

### ATTENTION (MUST READ)

- This product is designed and made exclusive for application models, do not use other models. Do not modify the way which is not listed or it will cause damage and trouble.
- We are not responsible for violation of law or damages and accidents caused by assembling mistake and improper setting.
- Please ask authorized mechanic for assembling and setting.
- Refer to the manufacturer service manual when installation.
- Bolts and nuts may get loosen by engine vibration. Make sure not to loosen any bolts and nuts before driving.
- This instruction sheet is for the instruction for stock condition.

### HOW TO TAKE CARE SCREEN

#### ⚠ ATTENTION

- Under direct sunlight, the deformation, fire, etc trouble might occur because of condensing phenomenon due to concave mirror effect. Be careful when parking.
- In case of parking under direct sunlight, please protect screen from direct sunlight by using soft cloth, etc.
- When windy day, it is easy to get effect by wind, please ride at reduced speed.
- In case of parking with body cover on, please choose shaded and well ventilated place. If park under the high heat with body cover on, temperature increases inside and it might cause of deformation.
- Be careful not to apply battery fluid and brake fluid. It breaks screen.
- Do not apply excessive force and hard bend. It might cause of broken.
- Please check regularly to make sure not to loosen and slip. Please do additional tightening in need.
- Welnut get aging by ultraviolet rays and aging. If deterioration is remarkable, please change to new one.
- If there is a hard scratch and break on screen, please change to new one because it might fall off.
- In case that screen gets dirt, wipe with soft cloth or sponge with lots of water. Do not use blush because screen is easy to get scratch.
- In case of screen gets heavy dirt, please use neutral detergent. Do not use abrasive powder, organic solvent, acid / alkaline detergent, gasoline, benzene, sinner, etc.



PACKING LIST			
FIGURE	NAME	CODE	QTY
1	SCREEN (T-01 / UNIVERSAL) SMOKE	670-9000101	x1
2	SCREEN STAY L /CL250	670-1870101	x1
3	SCREEN STAY R /CL250	670-1870102	x1
4	STEPPED COLLAR	670-1861103	x4
5	PAN HEAD (+) SCREW (B) M5x20	052-0503020	x4
6	WASHER (B) 12x5.2xT1.5mm	090-0914005	x8
7	WELNUT C550 M5x0.8	678-0500001	x4
8	CAP BOLT M5x25	050-0500025	x4

### HOW TO INSTALL

#### ※ADVICE

When installing, tighten each bolt temporarily. Then tighten firmly with adjusting balance of left and right.

- 1) Remove head light socket bolt.
- 2) Install stay with attached bolt, washer and spacer collar to socket bolt hole point temporarily.
- 3) Install screen to LR stay with attached welnut, screw and washer while adjusting left and right balance.
- 4) After adjusting all parts balance, tighten firmly each bolts.

#### ATTENTION!

- If there is a hard degradation like a blem, fatigue and wear etc on the reuse parts, please change to new ones.
- Before installation, make sure to match the hole position not to break head light cover.

