

FRONT FENDER KIT

CODE : (SILVER) 680-1320060

APPLICATION : DAX125 (JB04)

(CHROME) 680-1320090

Thank you for purchasing Kitaco product. Read and understand the instruction before installing.

ATTENTION (MUST READ)

- This product is for dress up. Do not use for other purposes.
- Do not modify the way which is not listed or it will cause damage and trouble.
- We are not responsible for violation of law or damages and accidents caused by assembling mistake and improper setting.
- Please ask authorized mechanic for assembling and setting.
- Refer to the manufacturer service manual when installation.
- Bolts and nuts may get loosen by engine vibration. Make sure not to loosen any bolts and nuts before riding.
- This product might get discolored/rust for ages as well as how to use. Please understand when using.

PACKING LIST				SL	CP
FIGURE	NAME		CODE	QTY	
1	FRONT FENDER	SILVER (SL)	680-1320001SL	x1	-
		CHROME (CP)	680-1320001CP	-	x1
2	F FORK COVER	(L) LEFT	680-1320002	x1	x1
3	F FORK COVER	(R) RIGHT	680-1320003	x1	x1
4	MAIN STAY		680-1320004	x1	x1
5	SIDE STAY	(L) LEFT	680-1320005	x1	x1
6	SIDE STAY	(R) RIGHT	680-1320006	x1	x1
7	SUB STAY		680-1320007	x1	x1
8	FLANGE COLLAR		680-1320008	x7	x7
9	BUTTON CAP BOLT	M6x15	060-0550015	x3	x3
10	FLANGE HEXAGON BOLT	M6x12	062-0561012	x4	x4
11	WASHER	6.5x16x1.6	090-0907006	x3	x3

HOW TO INSTALL

※ If there is a hard degradation like a blem, fatigue and wear etc on the reuse parts, please change to new ones.

REMOVING

- 1) Remove genuine front fender from bottom case bracket.
Remove brake hose crammer and rubber / collar (back side of right bottom case bracket) from fender.
- 2) Remove genuine fork guard installation bolt (each 3pcs on left and right).

INSTALLING

- 3) Assemble Kitaco fender together with main stay (4) and flange collar (8) with M6 bolts (9) (11).
- 4) Install Kitaco side stay (5) (6) and fork guard (2) (3) with genuine bolts to front side of bottom case bracket. (temporarily)
- 5) Install brake hose crammer and sub plate (7) to back side of bottom case bracket. (temporarily)
- 6) Finally, tighten each bolts firmly.

※ Tighten bolts alternately evenly.

- Make sure not to loosen any bolts before riding.

