

LED SHUTTLE BEAM	APPLICATION : UNIVERSAL DC12V (AC NOT USABLE)
CODE	
(CLEAR) 800-0710000	(YELLOW) 800-0710010
SPEC	
VOLTAGE : DC12V (AC NOT USABLE) / POWER CONSUMPTION:10w / CURRENT CONSUMPTION : 0.9A	
IRRADIATION METHOD:SPOT BEAM	
BRIGHTNESS : MAX800lumen / COLOR TEMPERATURE : 6000kelvin (in case of clear) *Other colors unable to measure	
HARNESS LENGTH:AROUND 300mm	
SPECIFICATION : ALUMINUM DIE CAST BODY / ACRYLIC LENS / STAY & BOLT SET	

Thank you for purchasing Kitaco product. Read and understand the instruction before installing.

ATTENTION (MUST READ)

- Do not modify the way which is not listed or it will cause damage and trouble.
 - We are not responsible for violation of law or damages and accidents caused by assembling mistake and improper setting.
 - Please ask authorized mechanic for assembling and setting. Ask a specialist at specialty shop if you do not understand the role of the surrounding parts.
 - Refer to the manufacturer service manual when installation.
 - Bolts and nuts may get loosen by engine vibration. Make sure not to loosen any bolts and nuts before driving.
- *Lens color (density) might be different, but it is a tolerance and not a defect. Please understand.
- *Alumite products get discolored/rust for ages as well as how to use. Please understand when using.

[IMPORTANT] ATTENTION WHEN USING!

- Condensation may occur because of temperature difference.
 - This product is not perfectly water proof. Please be careful when washing.
 - If installing to a lot of vibration place, it might be unable to bring out performance and in the worst case, it might be break. Please do anti-vibration, etc and install where can prevent from vibration. If installing next to the engine, it might malfunction because of vibration and heat.
- *We are not responsible for break because of heat and vibration.

ATTENTION TO LED PRODUCT!

- Compared to filament, LED is not worry about running out. However, power supply is not stable with motor bike, sometimes LED will not be on.
- ATTENTION TO BATTERY LESS AND SMALL BATTERY VEHICLE
Depending on the vehicle, it might break because of overvoltage. Measure the power supply voltage with circuit tester (with peak hold is good) both direct and alternate current and make sure it is under 13.8V. We are not responsible for breaking because of over voltage.

PACKING LIST			
NAME	CODE	QTY	REMARK
LED SHUTTLE BEAM	-	1	STAY / BOLT SET ATTACHED

REPLACEMENT PARTS			
NAME	CODE	QTY	REMARK
CLEAR	800-0710009	1	HEXAGON BOLT FOR BODY (TORQUE : 5N · m)
YELLOW	800-0710019	1	

ATTENTION WHEN INSTALLING

- 1)Install not to prevent handling.
- 2)When wiring, please do water proof treatment.
- 3)Do not over tighten when tightening stay / bolts firmly.
(TORQUE : 10N · m)

WIRING	
COLOR	POL
RED	+
BLACK	-



3-8-13 NAGATA,
HIGASHI-OSAKA,
OSAKA, JAPAN
<https://www.kitaco.co.jp/>

201110